REFORMULATED REDUCED POLLUTION DIESEL FUEL

Patent Number:

WO0012654

Publication date:

2000-03-09

Inventor(s):

PEDERSEN MICHAEL J

Applicant(s)::

ATLANTIC RICHFIELD CO (US)

Requested Patent:

™O0012654

Application Number: WO1999US18622 19990817

Priority Number(s): US19980145189 19980901 IPC Classification:

C10L1/00; C10L1/04; C10L1/08; C10L1/18; C10L7/20; F23C1/08

EC Classification:

C10G65/12, C10L1/08

Equivalents:

AU5488899, F EP1115814 (WO0012654), A1

Abstract

A reformulated diesel fuel, a method of making and a method of using the diesel fuel to reduce pollution are disclosed. The diesel fuel meets the requirements of ASTM D975-96a for a low sulfur number 2 diesel fuel and provides reduced emission benefits relative to a certified diesel fuel, certified under Section 2282(g) Title 13, California Code of Regulations and containing less than 15 volume percent aromatics having a natural centane number of at least 55, a sulfur content less than 15 ppmw, a nitrogen content less than 10 ppmw, a polycyclic aromatics content no greater than 1.5 weight percent and an initial boiling point of at least 350 degrees F. The method of making includes hydrotreating stream (12) in a vessel (10) and hydrocracking a stream (20) in a vessel (24) in order to obtain a diesel range fraction which is separated to obtain a diesel fuel (48) and a gasoline fraction (44).

Data supplied from the esp@cenet database - I2